

# TORQU3 AUTOMOTIVE FULLY SYNTHETIC AXLE GEAR OIL (GL5)

(High Quality Premium Axle Gearbox Oils)

TORQU3 Gearbox oils are automotive gear lubricants containing multi-functional additives required for mild extreme pressure conditions.

## PERFORMANCE BENEFITS PREMIUM FORMULATION

- Proven Gear Protection in low and high speed conditions.
- Superior Sulfur Phosphorus Additives.
- Contains additives to inhibit oil oxidation and lubricated parts clean.
- Contains inhibitors to protect against corrosion, rust and foaming.
- Reduces Cost Associated with seasonal oil Changes.

## APPLICATIONS

- Manual gear boxes of passenger cars and commercial vehicles operating under high speed/low torque and low speed/high torque conditions. Rear axles, suitable for applications presenting conditions of medium severity, such as light duty commercial vehicles and passenger cars. Not suitable for heavy duty hypoid axles.

## PACKAGING

- 1L , 4L , 5L , 6L 7L , 18L , 20L , 200L, 209L, 1000L

## MEETS SPECIFICATIONS & APPROVALS:

- API Service Classification GL-5
- API MT-1
- MACK GO-J
- MARITOR 076-A
- MARITOR 076-D
- MARITOR 076-Q
- AGMA 9005-E02
- CINCINNATI MACHINE
- SAE J2360
- MIL-PRF-2105E
- PG-2
- FORD WSP-M2C 197-A
- ASIT 224
- AGMA 9002 D94
- US STEEL
- DIN 51517:3
- CLEANLINESS PERFORMANCE IN OXIDATION TESTS

## Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

## TORQU3 FULLY SYNTHETIC AXLE GEAR OIL GL5

SAE Viscosity Grade	75W85	75W90	75W140
Kinematic viscosity at 40°C (cSt)	70.15	82.1	140.8
Kinematic viscosity at 100°C (cSt)	12.5	14.6	24.5
Density at 15°C	0.866	0.868	0.877
Flash point, °C	203	207	211
Pour point, °C	-40	-40	-37
Viscosity Index	179	186	209

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.