



TORQU3 AUTOMOTIVE SYNTHETIC AXLE GEAR OIL (GL5)

(High Quality Premium Axle Gearbox Oils)

TORQU3 Gearbox oils are automotive gear lubricants containing multi-functional additives required for mild extreme pressure conditions.

PERFORMANCE BENEFITS PREMIUM FORMULATION

- Contains additives to inhibit oil oxidation and lubricated parts clean. Contains inhibitors to protect against corrosion, rust and foaming.

APPLICATIONS

- Manual gear boxes of passenger cars and commercial vehicles operating under high speed/low torque and low speed/high torque conditions. Rear axles, suitable for applications presenting conditions of medium severity, such as light duty commercial vehicles and passenger cars. Not suitable for heavy duty hypoid axles.

PACKGING

- 1L , 4L , 5L ,6L 7L , 18L , 20L , 200L, 209L, 1000L

MEETS SPECIFICATIONS & APPROVALS:

- API Service Classification GL-5
- ZF-TE-ML05A/07A/08A/12E
- ZF TE-ML C-D
- ZF TE-ML 16B-19B
- MAN342N
- AGMA 9005-E02
- AISE 224
- DAVID BROWN S1.53.101
- DIN 51517PART3
- US STEEL 224
- AGMA 9005-D94
- ASIT 224
- FORD WSP-M2C197-A
- MERITOR 076-A/D/Q
- CINCINNATI MACHINE
- SAE J2360

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3 SYNTHETIC AXLE GEAR OIL GL5			
SAE Viscosity Grade	80W90	80W140	85W140
Kinematic viscosity at 40°C (cSt)	70.8	82.5	141.3
Kinematic viscosity at 100°C (cSt)	12.6	14.6	25.4
Density at 15°C	0.868	0.868	0.877
Flash point, °C	203	207	211
Pour point, °C	-40	-40	-37
Viscosity Index	180	187	210

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.