

TORQU3 PREMIUM HEAT TRANSFER OIL

[High Quality HEAT TRANSFER OIL]

TORQU3 SERIES IS A HIGH QUALITY HEAR TRANSFER OIL MADE WITH HIGH NATURE VISCOSITY FULLY SYNTHETUC BASE OIL AND HIGH TECHONOLGY CORE OXIDATION INHIBITOR ENHANCE THE HIGH TEMPERATURE PERFORMANCE AND STABILITY AS WELL AS PROLONG PRORUCTS LIFE SPAM.

BENEFITS & FEATURES:

- Excellent thermal eefficiency and stability.
- Good rust and corrosion protection.
- Excellent performance at temperature.
- Ease of pumping and circulation.
- Manimized makeup oil.

PACKGING

- 1L , 4L , 18L , 209L

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3 PREMIUM HEAT TRANSFER OIL

SAE Viscosity Grade	ISO VG 22	ISO VG 32	ISO VG 46
Kinematic viscosity at 40°C (cSt)	22.2	30.7	44.3
Kinematic viscosity at 100°C (cSt)	4.58	5.66	7.3
Density at 15°C	0.841	0.844	0.848
Flash point, °C	218	228	232
Pour point, °C	-19	-19	-16
Viscosity Index	122	128	127

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.