

TORQU3 PREMIUM AIR COMPRESSOR

(High Quality Premium Air Compressor Oil)

TORQU3 Air Compressor Oils is based on highly refined mineral oils, which are intended for the lubrication of both reciprocating and rotary air compressors.

PERFORMANCE BENEFITS

PREMIUM FORMULATION

GOOD WATER SEPARATION CHARACTERISTICS

- Allows condensation to readily separate from the oil, minimizing the risk of emulsions which could block the oil separator element.

FULLY INHIBITED AGAIN CORROSION

- Enables protection even when operating under humid conditions.

LOW DEPOSIT FORMING TENDENCIES

- Extends oil change intervals and provides longer air filter life which contributes to a reduction in maintenance costs.

APPLICATIONS

- Recommended for the lubrication of rotors, bearings and gears in rotary compressors as well as reciprocating air compressors.

PACKAGING

- 1L , 4L , 5L , 6L , 7L , 18L , 20L , 200L , 209L , 1000L

MEETS SPECIFICATIONS & APPROVALS:

- DIN 51506 VDL Specifications

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3 HIGH PERFORMANCE RECIPROCATING COMPRESSOR OIL

SAE Viscosity Grade	32	46	68	100	150
Kinematic viscosity at 40°C (cSt)	32.87	46.07	68.16	98.51	146
Kinematic viscosity at 100°C (cSt)	5.622	6.865	8.969	98.51	146
Density at 15°C	0.858	0.864	0.867	0.867	0.875
Flash point, °C	222	250	250	284	265
Pour point, °C	-36	-36	-42	-39	-30
Viscosity Index	109	104	106	107	104
RUST TEST , DISTILLED WATER	PASS	PASS	PASS	PASS	PASS

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.